Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in

the application:

Listing of Claims:

(Currently amended) In a data communication network supporting

data compression, a A method for optimizing compression efficiency[[,]] comprising:

filtering protocol-specific header and control information of a protocol data

unit (PDU) to determine compressibility of the contents of said protocol data unit

including determining if a given protocol data unit is associated with a previously

filtered protocol data unit by tracking previously filtered protocol data units and

information regarding the compression applied to previously filtered protocol data

units:

based on the result of said filtering, selecting the state of data link

compression for said protocol data unit to optimize compression efficiency such that

if the given protocol data unit is associated with a previously filtered protocol data

unit, the data link compression that was applied to for the previously filtered

protocol data unit is selected; and

associating the selected state of data link compression with the protocol data

unit to control a compression process adapted to compress contents of protocol data

units.

- 2 -

Applicant: Brooks et al. Application No.: 09/774,545

2. (Original) The method as claimed in claim 1, further including

compressing the contents of the protocol data unit as a function of the state of data

link compression.

3. (Original) The method as claimed in claim 2, wherein compressing

the contents of the protocol data unit includes applying an indication in or with the

compressed protocol data unit to indicate whether the contents of the protocol data

unit have been compressed.

4. (Original) The method as claimed in claim 3, further including

decompressing the compressed contents of the protocol data unit.

5. (Original) The method as claimed in claim 4, wherein, based on the

indication of whether the contents of the protocol data unit have been compressed,

decompressing the compressed contents of the protocol data unit is performed in a

manner previously negotiated.

6. (Original) The method as claimed in claim 1, further including

accessing a table having entries with specific media types deemed compression

limited.

- 3 -

 (Original) The method as claimed in claim 1, wherein filtering includes associating individual protocol data units to a specific media type.

8. (Cancelled)

- (Currently amended) The method as claimed in claim 1, wherein determining includes accessing a table including <u>tracking</u> information of <u>about</u> previously filtered protocol data units.
- 10. (Original) The method as claimed in claim 1, wherein selecting the state of the data link compression includes disabling the data link compression if the compressibility of the contents of the protocol data unit is determined to be low.
- 11. (Original) The method as claimed in claim 1, wherein selecting the state of the data link compression includes enabling the data link compression if the compressibility of the contents of the protocol data unit is determined to be high.
- 12. (Original) The method as claimed in claim 1, further including initializing a table used by the data link compression with data patterns expected to be contained in the content of said protocol data unit.

13. (Currently Amended) In a data communication network supporting

data compression, a An apparatus for optimizing compression efficiency [[,]]

comprising:

a protocol data unit (PDU) filter configured to determine compressibility of

the contents of a given protocol data unit by determining if the given protocol data

unit is associated with a previously filtered protocol data unit;

a tracking unit operatively associated with the PDU filter configured to track

previously filtered protocol data units to enable the PDU filter to determine if the

given protocol data unit is associated with a previously filtered protocol data unit:

and

a selector coupled to the output of the filter and configured (i) to select the

state of data link compression for the protocol data unit to optimize compression

efficiency such that if the given protocol data unit is associated with a previously

filtered protocol data unit, the data link compression that was applied to for the

previously filtered protocol data unit is selected; and (ii) to associate the selected

state of data link compression with the protocol data unit to control a compressor

adapted to compress contents of protocol data units.

14 (Previously presented) The apparatus as claimed in claim 13,

further including a compressor configured to compress the contents of the protocol

- 5 -

data unit responsive to the state of data link compression.

15. (Previously presented) The apparatus as claimed in claim 14,

wherein the compressor is configured to include an indication in or with the

compressed protocol data unit to indicate whether the contents of the protocol data

unit have been compressed.

16. (Previously presented) The apparatus as claimed in claim 15,

further including a decompressor configured to decompress the compressed contents

of the protocol data unit.

17. (Previously presented) The apparatus as claimed in claim 16,

wherein, the decompressor is configured to decompress the contents of the protocol

data unit in a manner previously negotiated with the compressor based on the

indication of whether the contents of the protocol data unit have been compressed.

18. (Previously presented) The apparatus according to claim 13.

wherein:

the filter is configured to determine compressibility of the contents of the

given protocol data unit by determining the type of data of the given protocol data

unit where the given protocol data unit is not associated with a previously filtered

- 6 -

protocol data unit; and

the selector is configured to select the state of data link compression for the

given protocol data unit based on the determined type of data of the given protocol

data unit if the given protocol data unit is not associated with a previously filtered

protocol data unit and includes a table configured to store entries with specific

media types deemed compression limited.

19. (Previously presented) The apparatus as claimed in claim 13,

wherein the filter is configured to associate individual protocol data units to a

specific media type.

20. (Cancelled)

21. (Currently amended) The apparatus as claimed in claim 13 20.

wherein the filter further includes a table configured to store information of about

previously filtered protocol data units.

22. (Previously presented) The apparatus as claimed in claim 13,

wherein the selector is configured to disable the compressor if the compressibility of

the contents of the protocol data unit is determined to be low.

- 7 -

23 (Previously presented) The apparatus as claimed in claim 13.

wherein the selector is configured to enable the compressor if the compressibility of

the contents of the protocol data unit is determined to be high.

24. (Previously presented) The apparatus as claimed in claim 13.

further including an initialization unit configured to initialize a table used by the

compressor with data patterns expected to be contained in the content of said

protocol data unit.

25.-27. (Cancelled)

A computer-readable medium having stored 28. (Currently Amended)

thereon sequences of instructions, the sequences of instructions including

instructions, when executed by a processor, configured to cause the processor to

perform:

filtering protocol-specific header and control information of a protocol data

unit to determine compressibility of the contents of said protocol data unit

including:

determining if a given protocol data unit is associated with a

previously filtered protocol data unit by tracking previously filtered protocol

data units and information regarding the compression applied to previously

- 8 -

filtered protocol data units; and

determining the type of data of the given protocol data unit where the

given protocol data unit is not associated with a previously filtered protocol

data unit;

selecting the state of data link compression for said protocol data unit based

on the results of said filtering to optimize compression efficiency such that:

if the given protocol data unit is associated with a previously filtered

protocol data unit, the data link compression that was applied to for the

previously filtered protocol data unit is selected; and

otherwise the state of data link compression is selected based on the

determined type of data of the given protocol data unit; and

associating the selected state of data link compression with the protocol data

unit to control a compression process adapted to compress contents of protocol data

units.

29.-31. (Cancelled)

32. (Previously presented) The method of claim 1 wherein:

the filtering protocol-specific header and control information of a protocol

data unit (PDU) to determine compressibility of the contents of said protocol data

unit includes determining the type of data of the given protocol data unit where the

given protocol data unit is not associated with a previously filtered protocol data

- 9 -

Applicant: Brooks et al. Application No.: 09/774,545

unit: and

the selecting the state of data link compression for said protocol data unit to optimize compression efficiency is performed such that the state of data link compression is selected based on the determined type of data of the given protocol data unit if the given protocol data unit is not associated with a previously filtered protocol data unit.